

# K-PUR-BREMSSPIRALE

PUR brake coil with connection

**HANSA FLEX**

## Caracteristici

<b>Racord 1 + 2</b>	Filet metric exterior cilindric
<b>Standard</b>	tested in accordance with DIN 74323 DIN 74324 ISO 7268-2 ISO 7375-2 DIN 73378 DIN 74310-2
<b>Aprobare</b>	German Technical Surveyance Association (TÜV)- type approved (Certificate R 9910199)
<b>Temperatură min.</b>	-40 °C
<b>Temperatură max.</b>	90 °C
<b>Material</b>	PUR



## Informații suplimentare

- will not break at fittings
- excellent antikink characteristics – kinking leaves no defects
- longer operation length
- highly resistant to tearing off at fittings
- excellent springback characteristics
- unplasticized so no embrittlement
- resistant to oil and grease
- resistant to UV and ozon
- service life many times longer than conventional coil tubing

## Articol

Denumire	G1 + G2	Ø interior (mm)	Ø exterior (mm)	Grosimea peretelui (mm)	Lungime (m)	Culoarea
K- 07 10 13 21	M 16 x 1,5	8,0	12,0	2,0	4,50	negru
K- 07 10 13 22	M 16 x 1,5	8,0	12,0	2,0	4,50	galben
K- 07 10 13 23	M 16 x 1,5	8,0	12,0	2,0	4,50	roșu
K- 07 10 13 24	M 16 x 1,5	8,0	12,0	2,0	5,50	negru
K- 07 10 13 25	M 16 x 1,5	8,0	12,0	2,0	5,50	galben
K- 07 10 13 26	M 16 x 1,5	8,0	12,0	2,0	5,50	roșu