K-PUR-BREMSSPIRALE

PUR brake coil with connection

Caracteristici

Racord 1 + 2	Filet metric exterior cilindric
Standard	tested in accordance with DIN 74323 DIN 74324 ISO 7268-2 ISO 7375-2 DIN 73378 DIN 74310-2
Aprobare	German Technical Surveyance Association (TÜV)-type upproved (Certificate R 9910199)
Temperatură min.	-40 °C
Temperatură max.	90 °C
Material	PUR



Informaţii suplimentare

- will not break at fittings
- excellent antikink characteristics – kinking leaves no defects
- longer operation length
- highly resistant to tearing off at fittings
- excellent springback characteristics
- unplasticized so no embrittlement
- resistant to oil and grease
- resistant to UV and ozon
- service life many times longer than conventional coil tubing

Articol

Denumire	G1 + G2	Ø interior (mm)	Ø exterior (mm)	Grosimea peretelui (mm)	Lungime (m)	Culoarea
K- 07 10 13 21	M 16 x 1,5	8,0	12,0	2,0	4,50	negru
K- 07 10 13 22	M 16 x 1,5	8,0	12,0	2,0	4,50	galben
K- 07 10 13 23	M 16 x 1,5	8,0	12,0	2,0	4,50	roşu
K- 07 10 13 24	M 16 x 1,5	8,0	12,0	2,0	5,50	negru
K- 07 10 13 25	M 16 x 1,5	8,0	12,0	2,0	5,50	galben
K- 07 10 13 26	M 16 x 1,5	8,0	12,0	2,0	5,50	roşu

În pofida controlului minuţios nu putem exclude eventualele informaţii eronate şi nu garantăm pentru datele cuprinse.