


K-MANO ABSPH ZAPF DREH MUF2

Pressure gauge stopcocks, male - loose (rotatable) female

Caracteristici

| | |
|-----------------------------|---|
| Utilizare | For all pressure gauges with a flat gasket acc. to DIN 16258 |
| Domeniu de presiune | Max. 16 bar, depending on the variant Pressure gauge valves should be used for higher pressures |
| Temperatură | Max. +50 °C |
| Carcasă | Brass with a bare metal surface or stainless steel 1.4571 |
| Mâner | Plastic |
| Flanșă de verificare | - |



Indicație

K-07201090, K-07201091 in acc. with DIN 16261-A, K-07201096, K-07201097 in acc. with DIN 16261-B
K-07201128, K-07201129 in acc. with DIN 16262-A, K-07201127 in acc. with DIN 16262-B
Alte date sunt disponibile la cerere.

Descriere

It is useful to install a stopcock as a shut-off element between the pressure gauge and the pipe. When the lever is set to the »blow out« position, the medium is discharged into the atmosphere. Stopcocks with a test port allow pressure gauges to be simultaneously connected to the pipe.

Informații suplimentare

Further measuring ranges on request

Version for panel mounting available on request. Version with max. pointer available on request

Articol

| Denumire | Filet | PN (bar) | SW (mm) | Material |
|----------------|-------|----------|---------|----------|
| K- 07 20 11 17 | G 1/2 | 25 | 27 | Alamă |
| K- 07 20 11 18 | G 1/2 | 25 | 27 | Alamă |