

# K-MANO ABSPV ZAPF SPAN MUF PRUEFFL

Pressure gauge valves, male - female/female, with test flange 60 x 25 x 10

**HANSA FLEX**

## Caracteristici

|                                     |  |
|-------------------------------------|--|
| Presiune de lucru                   | max. 250 bar brass, max. 400 bar steel/<br>stainless steel         |
| Temperatură                         | Max. +120 °C with brass/steel;<br>Max. +200 °C for stainless steel |
| Material pentru toate componentele  | Stainless steel  |
| Material de etanșare                | PTFE   |
| Carcasă                             | Brass, black-finished steel or stainless<br>steel 1.4571           |
| Rotiță de reglare                   | Plastic  |
| Piuliță olandeză mufă de tensionare | Steel  |
| Ax de supapă, con de supapă         | Stainless steel  |



## Indicație

Alte date sunt disponibile la cerere.

## Descriere

They are used as shut-off or reducing elements for pressure gauges when measuring liquids, gases or steam.

## Articol

| Denumire       | Filet | PN (bar) | SW<br>(mm) | Material        |
|----------------|-------|----------|------------|-----------------|
| K- 07 20 11 34 | G 1/2 | 250      | 27         | Alamă           |
| K- 07 20 11 33 | G 1/2 | 400      | 27         | Stainless steel |