

# K-RMM HFR STAHLBLECH SCHW

Standard pressure gauges with black sheet-steel bezel, connection on rear

**HANSA FLEX**

## Caracteristici

|                                                     |                                                                                                                                                     |
|-----------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| Tip                                                 | 111.12                                                                                                                                              |
| Execuție                                            | Bourdon-tube pressure gauge, standard design, mounting ring<br>Chromium plated sheet steel<br>Steel chrome plated or black or with triangular bezel |
| Utilizare                                           | gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise                                        |
| Clasă de calitate                                   | 1,6                                                                                                                                                 |
| Temperatură mediu                                   | max. +60 °C                                                                                                                                         |
| Temperatură ambientală                              | -20 °C până la +60 °C                                                                                                                               |
| Carcasă                                             | Sheet steel                                                                                                                                         |
| Material element de măsurare și mecanism arătătoare | aliaj de cupru                                                                                                                                      |
| Fereastră de vizitare                               | Transparent plastic                                                                                                                                 |



## Indicație

Alte date sunt disponibile la cerere.

## Articol

| Denumire       | Domeniu de măsurare | Ø (mm) | Racord |
|----------------|---------------------|--------|--------|
| K- 07 20 04 27 | -1 / 0.0 bar        | 40,0   | G 1/8  |
| K- 07 20 04 28 | 0 - 1.0 bar         | 40,0   | G 1/8  |
| K- 07 20 04 29 | 0 - 1.6 bar         | 40,0   | G 1/8  |
| K- 07 20 04 30 | 0 - 2.5 bar         | 40,0   | G 1/8  |
| K- 07 20 04 31 | 0 - 4.0 bar         | 40,0   | G 1/8  |
| K- 07 20 04 32 | 0 - 6.0 bar         | 40,0   | G 1/8  |
| K- 07 20 04 33 | 0 - 10.0 bar        | 40,0   | G 1/8  |
| K- 07 20 04 34 | 0 - 16.0 bar        | 40,0   | G 1/8  |
| K- 07 20 04 35 | 0 - 25.0 bar        | 40,0   | G 1/8  |
| K- 07 20 04 36 | 0 - 40.0 bar        | 40,0   | G 1/8  |
| K- 07 20 05 30 | -1 / 0.0 bar        | 50,0   | G 1/4  |
| K- 07 20 05 31 | 0 - 1.0 bar         | 50,0   | G 1/4  |
| K- 07 20 05 32 | 0 - 1.6 bar         | 50,0   | G 1/4  |
| K- 07 20 05 33 | 0 - 2.5 bar         | 50,0   | G 1/4  |
| K- 07 20 05 34 | 0 - 4.0 bar         | 50,0   | G 1/4  |
| K- 07 20 05 35 | 0 - 6.0 bar         | 50,0   | G 1/4  |
| K- 07 20 05 36 | 0 - 10.0 bar        | 50,0   | G 1/4  |
| K- 07 20 05 37 | 0 - 16.0 bar        | 50,0   | G 1/4  |
| K- 07 20 05 38 | 0 - 25.0 bar        | 50,0   | G 1/4  |
| K- 07 20 05 39 | 0 - 40.0 bar        | 50,0   | G 1/4  |
| K- 07 20 05 40 | 0 - 60.0 bar        | 50,0   | G 1/4  |