

K-RMM HKR STAHL

Standard pressure gauges with 3-hole bezel, chrome-plated steel, dual scale in bar/psi and clamp fixing, connection on rear

HANSA FLEX

Caracteristici

Tip	111.12
Execuție	Bourdon-tube pressure gauge, standard design, mounting ring Chromium plated sheet steel Steel chrome plated or black or with triangular bezel
Utilizare	gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise
Clasă de calitate	2,5
Temperatură mediu	max. +60 °C
Temperatură ambientală	-20 °C până la +60 °C
Carcasă	Sheet steel
Material element de măsurare și mecanism arătătoare	aliaj de cupru
Fereastră de vizitare	Transparent plastic



Indicație

Alte date sunt disponibile la cerere.

Articol

Denumire	Domeniu de măsurare	Ø (mm)	Racord
K- 07 20 04 04	-1 / 0.0 bar	40,0	G 1/8
K- 07 20 04 05	0 - 1.0 bar	40,0	G 1/8
K- 07 20 04 06	0 - 1.6 bar	40,0	G 1/8
K- 07 20 04 07	0 - 2.5 bar	40,0	G 1/8
K- 07 20 04 08	0 - 4.0 bar	40,0	G 1/8
K- 07 20 04 09	0 - 6.0 bar	40,0	G 1/8
K- 07 20 04 10	0 - 10.0 bar	40,0	G 1/8
K- 07 20 04 11	0 - 16.0 bar	40,0	G 1/8
K- 07 20 04 12	0 - 25.0 bar	40,0	G 1/8