

K-RMM U KUNSTSTOFF MZ

Standard pressure gauges, connection radial on bottom

HANSA FLEX

Caracteristici

Tip	111.10 (radial connector on bottom)
Execuție	Bourdon-tube pressure gauge in standard design
Utilizare	gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise
Clasă de calitate	1.6 (Art No. K-07200303, K-07403298 - K-07201188: 2.5)
Ac indicator	(for Ø 160 mm - red pointer on the scale) red pointer to the window. For measuring ranges 0...0,6 bar bis 0...60 bar
Temperatură mediu	max. +60 °C
Temperatură ambientală	-20 °C până la +60 °C
Carcasă	Plastic
Material element de măsurare și mecanism arătătoare	aliaj de cupru
Fereastră de vizitare	Transparent plastic



Indicație

Alte date sunt disponibile la cerere.

Articol

Denumire	Domeniu de măsurare	Ø (mm)	Racord
K- 07 20 03 03	-1200 / 0.0 mbar	100,0	G 1/2"
K- 07 20 03 04	-1 / 0.0 bar	100,0	G 1/2"
K- 07 20 03 05	-1 / +0.6 bar	100,0	G 1/2"
K- 07 20 03 06	-1 / +1.5 bar	100,0	G 1/2"
K- 07 20 03 07	-1 / +3.0 bar	100,0	G 1/2"
K- 07 20 03 08	-1 / +5.0 bar	100,0	G 1/2"
K- 07 20 03 09	-1 / +9.0 bar	100,0	G 1/2"
K- 07 20 02 84	0 - 0.6 bar	100,0	G 1/2"
K- 07 20 02 85	0 - 1.0 bar	100,0	G 1/2"
K- 07 20 02 86	0 - 1.6 bar	100,0	G 1/2"
K- 07 20 02 87	0 - 2.5 bar	100,0	G 1/2"
K- 07 20 02 88	0 - 4.0 bar	100,0	G 1/2"
K- 07 20 02 89	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 02 90	0 - 10.0 bar	100,0	G 1/2"
K- 07 20 02 91	0 - 16.0 bar	100,0	G 1/2"
K- 07 20 02 92	0 - 25.0 bar	100,0	G 1/2"
K- 07 20 02 93	0 - 40.0 bar	100,0	G 1/2"
K- 07 20 11 86	0 - 60.0 bar	100,0	G 1/2"
K- 07 20 11 87	0 - 100.0 bar	100,0	G 1/2"
K- 07 20 11 88	0 - 160.0 bar	100,0	G 1/2"