


### Caracteristici

Presiune de lucru	max. 18 bar
Domeniu de temperaturi	0 °C to +60 °C
Toleranță presiune	± 0.3 bar at 10 l/min
Carcasă	Zinc
restul pieselor	Brass, NBR, stainless steel



### Indicație

Alte date sunt disponibile la cerere.

### Descriere

This single-acting diaphragm regulator can be installed in any pneumatic system. Since the pressure is preset in the factory and cannot be altered, the product is also tamper-proof. We recommend mounting the regulator directly on the tool to make sure the correct pressure is applied. In this case, the tool is never stressed by the higher pressure of the supply system and is protected against pressure fluctuations in hoses, pipes, etc. Energy efficiency and economic efficiency can be achieved by using an inline pressure regulator.

### Articol

Denumire	Filet	Presiune de lucru setată în prealabil	A (mm)	B	SW (mm)
K-07 25 02 75	G 1/4	1 bar	34,0	52,0 mm	17
K-07 25 02 76	G 1/4	2 bar	34,0	52,0 mm	17
K-07 25 02 77	G 1/4	3 bar	34,0	52,0 mm	17
K-07 25 02 78	G 1/4	4 bar	34,0	52,0 mm	17
K-07 25 02 79	G 1/4	5 bar	34,0	52,0 mm	17
K-07 25 02 80	G 1/4	6 bar	34,0	52,0 mm	17
K-07 25 02 81	G 1/4	6,5 bar	34,0	52,0 mm	17
K-07 25 02 82	G 1/4	7 bar	34,0	52,0 mm	17