

K-TR PA 612

Plastic pipes made of polyamide PA 12 (10 pcs.)

HANSA FLEX

Caracteristici

Temperatura de lucru	-60 °C to +100 °C (PA 12)
Caracteristici	Resistant to corrosion, vibration, impact, ageing, high pressures and heat
Lungime țevă	3 m
Unitate de ambalaj	10 lengths (O.D. 28 mm in packs of 5 lengths), only sold in complete packaging units!
Material	Polyamid PA 12, hard (according to DIN 73378)



Indicație

Operating pressure with 2.5 x overpressure safety!

Alte date sunt disponibile la cerere.

Descriere

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

Articol

Denumire	Ø exterior țevă (mm)	Ø interior țevă (mm)	Presiune de lucru max. la 20°C (bar)	Culoarea
K- 07 10 04 57	12	9	38	albastru
K- 07 10 04 59	12	9	38	negru
K- 07 10 04 61	15	12	25	albastru
K- 07 10 04 63	15	12	25	negru
K- 07 10 04 65	18	14	28	albastru
K- 07 10 04 67	18	14	28	negru
K- 07 10 04 69	22	18	22	albastru
K- 07 10 04 71	22	18	22	negru
K- 07 10 04 73	28	23	20	albastru
K- 07 10 04 75	28	23	20	negru