

K-TR PA 12

Plastic pipes made of polyamide PA 12 (20 pcs.)

HANSA FLEX

Caracteristici

Temperatura de lucru	-60 °C to +100 °C (PA 12)
Caracteristici	Resistant to corrosion, vibration, impact, ageing, high pressures and heat
Lungime țevă	3 m
Unitate de ambalaj	20 lengths (O.D. 28 mm in packs of 10 lengths), only sold in complete packaging units!
Material	Polyamid PA 12, hard (according to DIN 73378)



Indicație

Operating pressure with 2.5 x overpressure safety!

Alte date sunt disponibile la cerere.

Descriere

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

Articol

Denumire	Ø exterior țevă (mm)	Ø interior țevă (mm)	Presiune de lucru max. la 20°C (bar)	Culoarea
K- 07 10 04 56	12	9	38	albastru
K- 07 10 04 58	12	9	38	negru
K- 07 10 04 60	15	12	25	albastru
K- 07 10 04 62	15	12	25	negru
K- 07 10 04 64	18	14	28	albastru
K- 07 10 04 66	18	14	28	negru
K- 07 10 04 68	22	18	22	albastru
K- 07 10 04 70	22	18	22	negru
K- 07 10 04 72	28	23	20	albastru
K- 07 10 04 74	28	23	20	negru