# K-TR PU FU

Anti-spark PU hose

## Caracteristici

| | |
|---|---|
| **Presiune de lucru** | Dependent on temperature: 12 bar at 24 °C, 5 bar at 66 °C |
| **Culoarea** | negru |
| **Temperatură** | -40 °C to +70 °C |



## Indicaţie

Alte date sunt disponibile la cerere.

## Descriere

Blue polyurethane hose with an outer sheath made of black synthetic resin material. This sheath protects the inner PU tube from welding sparks. The sheath is not attached to the inner tube and can therefore be easily removed to enable conventional fittings to be installed. Protects against welding sparks, extremely flexible and non-kinking, resistant to a large number of chemicals, oils, greases, acids, bases, heat, ageing, UV light.

## Articol

| Denumire | Ø furtun interior (mm) | Ø furtun exterior (mm) | Grosimea peretelui (mm) |
|---|---|---|---|
| **K- 07 10 03 59** | 4,0 | 6,0 | 1,0 |
| **K- 07 10 03 60** | 5,0 | 8,0 | 1,5 |
| **K- 07 10 03 61** | 8,0 | 12,0 | 2,0 |

*În pofida controlului minuțios nu putem exclude eventualele informații eronate și nu garantăm pentru datele cuprinse.*