K-SPIR SCHL DREH VERSCHRAU

Spiral hose, with swivel adapter and kink protector



Caracteristici

Temperatura de lucru -40 °C to +74 °C



Indicație

Alte date sunt disponibile la cerere.

Descriere

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.

Articol						
Denumire	Filet	Ø furtun interior	Ø furtun exterior	Ø spiră exterioară	Max. working pressure resistance at 23°C	Lungime max. de lucru
		(mm)	(mm)	(mm)	(bar)	(m)
K- 07 10 07 19	G 1/4	5,0	8,0	40	10	3,0
K- 07 10 07 20	G 1/4	5,0	8,0	40	10	6,0
K- 07 10 07 21	G 1/4	5,0	8,0	40	10	7,5
K- 07 10 07 22	G 1/4	6,3	9,5	60	10	3,0
K- 07 10 07 23	G 1/4	6,3	9,5	60	10	6,0
K- 07 10 07 24	G 1/4	6,3	9,5	60	10	7,5
K- 07 10 12 77	G 1/4	6,3	9,5	60	10	10,0
K- 07 10 07 25	G 3/8	8,0	12,0	80	9	3,0
K- 07 10 07 26	G 3/8	8,0	12,0	80	9	6,0
K- 07 10 07 27	G 3/8	8,0	12,0	80	9	7,5
K- 07 10 12 86	G 3/8	8,0	12,0	80	9	10,0

Accesorii

K-DREHBARE VERSCHRAUBUNG Swivel adapters