K-SPIR SCHL DREH VERSCHRAU V

Spiral hose, with swivel adapter and kink protector, braided

Caracteristici

Tip de racord	with kink protector, swivel type
Temperatura de lucru	-40 °C to +74 °C



Indicaţie

Alte date sunt disponibile la cerere.

Descriere

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.

Articol

Denumire	Filet	Ø furtun interior (mm)	Ø furtun exterior (mm)	Ø spiră exterioară (mm)	Max. working pressure resistance at 23°C (bar)	Lungime max. de lucru (m)
K- 07 10 07 43	G 1/4	6,3	9,5	42	14	3,0
K- 07 10 07 44	G 1/4	6,3	9,5	42	14	6,0
K- 07 10 07 45	G 1/4	6,3	9,5	42	14	7,5
K- 07 10 07 46	G 3/8	8,0	12,0	55	14	3,0
K- 07 10 07 47	G 3/8	8,0	12,0	55	14	6,0
K- 07 10 07 48	G 3/8	8,0	12,0	55	14	7,5

Accesorii

K-DREHBARE VERSCHRAUBUNG	Swivel adapters

În pofida controlului minuțios nu putem exclude eventualele informații eronate și nu garantăm pentru datele cuprinse.