
K-SPIR SCHL KUPPL SET

Spiral hose and coupling kits

Caracteristici

Presiune de lucru	max. 10 bar (to the temperature +20 °C); max. 7 bar (at temperature +40 °C); max. 5 bar (at temperature +60 °C)
Cuplaj	High quality hand quick release coupling of steel for high flow rates For demanding applications with high mechanical wear
Furtun spiral	Polyurethane



Indicaţie

Alte date sunt disponibile la cerere.

Descriere

For pneumatic applications in challenging industrial environments. High-quality, one-hand quick disconnect coupling made of steel with safety lock to prevent unintentional disconnection. For complex applications susceptible to severe mechanical wear. The outer layer of the hose, which is designed to withstand flying sparks and scorching, has special spark protection. It is therefore ideal for all pneumatic tools used in welding processes.

Articol

Denumire	Dimensiune furtun	Ø spirală (mm)	Lungime de lucru (m)
K- 07 10 07 56	10 mm x 6,5 mm	52	4,0
K- 07 10 07 57	10 mm x 6,5 mm	52	6,0
K- 07 10 07 58	12 mm x 8 mm	65	8,0

În pofida controlului minuțios nu putem exclude eventualele informații eronate și nu garantăm pentru datele cuprinse.