K-VSEH 3-KRAFT

Receptacle combinations »3-Kraft«

Caracteristici

Carcasă	Amaplast with hinged cover
Integrat în carcasă	Hanging eyelets, wall mounting fixing and standing feet
Execuţie	Pre-wired
Intrări linii	Top: 1 x M 32, 1 x M 25, 2 x M 20; Side: 1 x M 25; One opening at the top for pneumatic connection or grabrails (all introductions to break)
Tip de protecţie	IP 44



Indicaţie

Alte date sunt disponibile la cerere.

Descriere

Receptacle combination with low power, high power or combined connections. Equipped with a pneumatic connection (DN 7.2 coupling with 9 mm stem).

Articol

Denumire	Echipare	Culoarea
K- 07 10 03 50	3 Schuko socket 16 A 2p + E 230 V	galben
K- 07 10 03 49	2 Schuko socket 16 A 2p + E 230 V, 1 CEEform socket 16 A 5p 400 V	argint

Accesorii

K-VT 2 KUPPL 7,2 STECKNIP MS	Distributors with 2 quick disconnect couplings DN 7.2, brass with push in plug DN 7.2 - DN 7.8
K-ZUBEH VSEH 3 KRAFT AIRKRAFT	Accessories for receptacle combinations »3-Kraft« and »airkraft«

În pofida controlului minuţios nu putem exclude eventualele informaţii eronate şi nu garantăm pentru datele cuprinse.