


K-VERSCHLUSSNIPPEL IG MS

Self-sealing plugs, brass

HANSA FLEX

Caracteristici

Presiune de lucru	See table. All values referred to a medium temperature of 50 °C (static working pressure)
Debit aer	440 l/min (G 1/8), 840 l/min (G 1/4), 1.280 l/min (G 3/8), 1.950 l/min (G 1/2), 4.500 l/min (G 3/4) (at 6 bar and $\Delta p = 0,5$ bar)
Temperatură mediu	-20 °C to +100 °C
Carcasă, manșon, supapă	Brass
Arc, inel elastic, bile	stain less steel
Material de etanșare	NBR



Indicație

Alte date sunt disponibile la cerere.

Descriere

Hydraulic couplings, both sides sealing, for liquid media acc. to ISO 7241, B Series.

Articol

Denumire	Racord	NW	Presiune de lucru (bar)	Lungime (mm)	SW (mm)
K- 07 40 10 15	G 1/8 female	4,3	250,0	29,5	14
K- 07 40 10 16	G 1/4 female	6,3	200,0	35,3	19
K- 07 40 10 17	G 3/8 female	7,5	200,0	39,0	22
K- 07 40 10 18	G 1/2 female	11,0	150,0	48,0	27
K- 07 40 10 19	G 3/4 female	13,0	100,0	60,0	36