
K-VERSCHLUSSNIPPEL IG POM

Self-sealing plugs, POM

Caracteristici

Presiune de lucru	See table. All values referred to a medium temperature of 50 °C (static working pressure)
Debit aer	440 l/min (G 1/8), 840 l/min (G 1/4), 1.280 l/min (G 3/8), 1.950 l/min (G 1/2), 4.500 l/min (G 3/4) (at 6 bar and Δp = 0,5 bar)
Temperatură mediu	-20 °C to +90 °C
Carcasă, manşon	POM (Delrin), white
Supapă	Stainless steel 1.4305
Arc, inel elastic, bile	stain less steel
Material de etanşare	NBR



Indicaţie

Alte date sunt disponibile la cerere.

Descriere

Hydraulic couplings, both sides sealing, for liquid media acc. to ISO 7241, B Series.

Articol

Denumire	Racord	Presiune de lucru (bar)	Lungime (mm)	NW	SW (mm)
K- 07 40 39 58	G 1/8 female	15,0	29,5	4,3	14
K- 07 40 39 59	G 1/4 female	15,0	35,3	6,0	19
K- 07 40 39 60	G 3/8 female	15,0	39,0	7,5	22
K- 07 40 39 61	G 1/2 female	10,0	48,0	11,0	27
K- 07 40 39 62	G 3/4 female	10,0	60,0	13,0	36

În pofida controlului minuțios nu putem exclude eventualele informații eronate și nu garantăm pentru datele cuprinse.