

K-LKM 5 UWB

Non-interchangeable quick disconnect couplings DN 5

HANSA FLEX

Caracteristici

Presiune de lucru	0 - 35 bar, maximum static working pressure (non-pulsating)
Debit aer	560 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Temperatură mediu	-20 °C to +100 °C
Manșon de deblocare	Anodised aluminium
Arc, inel elastic, bile	stain less steel
Material de etanșare	NBR



Indicație

Standard push-in plugs for couplings DN 5 and DN 7.2 – DN 7.8 are compatible with these non-interchangeable couplings.

Alte date sunt disponibile la cerere.

Descriere

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

Articol

Denumire	Racord	Culoarea	Lungime (mm)	SW (mm)
K- 07 35 06 80	G 1/8 male	verde	45,0	14
K- 07 35 06 81	G 1/4 male	verde	47,0	17
K- 07 35 06 82	G 1/8 female	verde	45,0	14
K- 07 35 06 83	G 1/4 female	verde	47,0	17
K- 07 35 06 84	G 1/8 male	Brown	45,0	14
K- 07 35 06 85	G 1/4 male	Brown	47,0	17
K- 07 35 06 86	G 1/8 female	Brown	45,0	14
K- 07 35 06 87	G 1/4 female	Brown	47,0	17
K- 07 35 06 88	G 1/8 male	albastru	45,0	14
K- 07 35 06 89	G 1/4 male	albastru	47,0	17
K- 07 35 06 90	G 1/8 female	albastru	45,0	14
K- 07 35 06 91	G 1/4 female	albastru	47,0	17
K- 07 35 06 92	G 1/8 male	roșu	45,0	14
K- 07 35 06 93	G 1/4 male	roșu	47,0	17
K- 07 35 06 94	G 1/8 female	roșu	45,0	14
K- 07 35 06 95	G 1/4 female	roșu	47,0	17