


K-LKM 7,8 UWB

Non-interchangeable quick disconnect couplings DN 7.8

HANSA FLEX

Caracteristici

Presiune de lucru	0 - 35 bar, maximum static working pressure (non-pulsating)
Debit aer	1.800 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Temperatură mediu	-20 °C to +100 °C
Carcasă	Brass
Supapă	Die-cast zinc, nickel-plated
Manșon de deblocare	Anodised aluminium
Arc, inel elastic, bile	stain less steel
Material de etanșare	NBR



Indicație

Standard push-in plugs for couplings DN 5 and DN 7.2 – DN 7.8 are compatible with these non-interchangeable couplings.

Alte date sunt disponibile la cerere.

Descriere

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

Articol

Denumire	Racord	Culoarea	Lungime (mm)	SW (mm)
K- 07 35 08 01	G 1/4 male	verde	57,5	19
K- 07 35 08 02	G 3/8 male	verde	57,5	19
K- 07 35 08 03	G 1/4 female	verde	55,5	19
K- 07 35 08 04	G 3/8 female	verde	54,5	19
K- 07 35 08 05	G 1/4 male	Brown	57,5	19
K- 07 35 08 06	G 3/8 male	Brown	57,5	19
K- 07 35 08 07	G 1/4 female	Brown	55,5	19
K- 07 35 08 08	G 3/8 female	Brown	54,5	19
K- 07 35 08 09	G 1/4 male	albastru	57,5	19
K- 07 35 08 10	G 3/8 male	albastru	57,5	19
K- 07 35 08 11	G 1/4 female	albastru	55,5	19
K- 07 35 08 12	G 3/8 female	albastru	54,5	19
K- 07 35 08 13	G 1/4 male	roșu	57,5	19
K- 07 35 08 14	G 3/8 male	roșu	57,5	19
K- 07 35 08 15	G 1/4 female	roșu	55,5	19
K- 07 35 08 16	G 3/8 female	roșu	54,5	19