
K-LKM 7,8 UWB

Non-interchangeable quick disconnect couplings DN 7.8

Caracteristici

Presiune de lucru	0 - 35 bar, maximum static working pressure (non-pulsating)
Debit aer	1.800 l/min (at 6 bar and Δp = 0.5 bar)
Temperatură mediu	-20 °C to +100 °C
Carcasă	Brass
Supapă	Die-cast zinc, nickel-plated
Manşon de deblocare	Anodised aluminium
Arc, inel elastic, bile	stain less steel
Material de etanşare	NBR



Indicaţie

Standard push-in plugs for couplings DN 5 and DN 7.2 – DN 7.8 are compatible with these non-interchangeable couplings.
Alte date sunt disponibile la cerere.

Descriere

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

Articol

Denumire	Racord	Culoarea	Lungime (mm)	SW (mm)
K- 07 35 08 01	G 1/4 male	verde	57,5	19
K- 07 35 08 02	G 3/8 male	verde	57,5	19
K- 07 35 08 03	G 1/4 female	verde	55,5	19
K- 07 35 08 04	G 3/8 female	verde	54,5	19
K- 07 35 08 05	G 1/4 male	Brown	57,5	19
K- 07 35 08 06	G 3/8 male	Brown	57,5	19
K- 07 35 08 07	G 1/4 female	Brown	55,5	19
K- 07 35 08 08	G 3/8 female	Brown	54,5	19
K- 07 35 08 09	G 1/4 male	albastru	57,5	19
K- 07 35 08 10	G 3/8 male	albastru	57,5	19
K- 07 35 08 11	G 1/4 female	albastru	55,5	19
K- 07 35 08 12	G 3/8 female	albastru	54,5	19
K- 07 35 08 13	G 1/4 male	roşu	57,5	19
K- 07 35 08 14	G 3/8 male	roşu	57,5	19
K- 07 35 08 15	G 1/4 female	roşu	55,5	19
K- 07 35 08 16	G 3/8 female	roşu	54,5	19

În pofida controlului minuțios nu putem exclude eventualele informații eronate și nu garantăm pentru datele cuprinse.