

K-INLINE-EJEKTTOREN SLP

Inline ejectors »SLP«, plug connection

Caracteristici

Caracteristici	Vacuum generator with high maximum vacuum level (85% vacuum) No moving parts, which means no wear and no maintenance ultra small footprint, suitable for confined spaces minimal air consumption \nlow noise
Utilizare	by screwing / plugging into the distribution beam direct attachment to the suction pad for handling various workpieces
Carcasă	plastic (Typ SLP)
Sistem de duze	Brass (type VR)
Racord	thread connector





Indicaţie

Alte date sunt disponibile la cerere.

Descriere

For vacuum generation directly at the point of use. For direct installation between the suction pad and the compressed air supply. Purely pneumatic vacuum generator that operates on the Venturi principle. Compressed air enters the ejector and flows through a nozzle. This results in a vacuum immediately behind the nozzle outlet, and air is drawn in through the vacuum inlet. This air and the driving air leave the ejector and enter the atmosphere via the exhaust air outlet.

Articol

Denumire	Dimensiune duză	Racord pentru aer evacuat	Racord de aer comprimat	Racord de vid	Grad de evacuare	Consum de aer la aspirare (L/min)	Capacitate max. de aspirare (L/min)	Lungime (mm)	Presiune de lucru (bar)
K- 07 45 01 27	0,5	-	4 mm	4 mm	85 %	13,0	8,0	57,0	4,5
K- 07 45 01 28	0,7	-	4 mm	4 mm	85 %	25,0	16,0	57,0	4,5

În pofida controlului minuțios nu putem exclude eventualele informații eronate și nu garantăm pentru datele cuprinse.