

K-FEDERSTOESSEL

Spring plungers

HANSA FLEX

Caracteristici

Utilizare	Handling of workpieces with differing heights (eg. Curved metal sheets) Handling of very sensitive workpieces, very soft landing is assured
Temperatură min.	0 °C
Temperatură max.	80 °C
Racord aspirator	M 3 female
Execuție	Spring plunger with high-strength steel rod, guide sleeve and lower damping spring Plunger rod with integrated vacuum guide
Cursă arc	5,0 mm



Indicație

Alte date sunt disponibile la cerere.

Descriere

Suitable for all round or oval suction pads in our standard range.

Articol

Denumire	Racord de vid	Lungime (mm)	Încărcare pe verticală (N/m ²)
K- 07 45 00 73	M 3 female	33,5	550
K- 07 45 00 76	M 5 female	41,2	1500
K- 07 45 00 74	M 5 female	47,2	1500
K- 07 45 00 75	M 5 female	59,2	1500
K- 07 45 00 70	G 1/8 female	80,0	3700
K- 07 45 00 67	G 1/8 female	95,0	3700
K- 07 45 00 71	G 1/8 female	93,0	3700
K- 07 45 00 68	G 1/8 female	124,5	2400
K- 07 45 00 72	G 1/8 female	124,0	2400
K- 07 45 00 69	G 1/8 female	154,0	2400