

# K-FEDERSTOESSEL

Spring plungers

**HANSA FLEX**

## Caracteristici

<b>Utilizare</b>	Handling of workpieces with differing heights (eg. Curved metal sheets) Handling of very sensitive workpieces, very soft landing is assured
<b>Temperatură min.</b>	0 °C
<b>Temperatură max.</b>	80 °C
<b>Racord aspirator</b>	M 3 female
<b>Execuție</b>	Spring plunger with high-strength steel rod, guide sleeve and lower damping spring Plunger rod with integrated vacuum guide
<b>Cursă arc</b>	5,0 mm



## Indicație

Alte date sunt disponibile la cerere.

## Descriere

Suitable for all round or oval suction pads in our standard range.

## Articol

Denumire	Racord de vid	Lungime (mm)	Încărcare pe verticală (N/m <sup>2</sup> )
K- 07 45 00 73	M 3 female	33,5	550
K- 07 45 00 76	M 5 female	41,2	1500
K- 07 45 00 74	M 5 female	47,2	1500
K- 07 45 00 75	M 5 female	59,2	1500
K- 07 45 00 70	G 1/8 female	80,0	3700
K- 07 45 00 67	G 1/8 female	95,0	3700
K- 07 45 00 71	G 1/8 female	93,0	3700
K- 07 45 00 68	G 1/8 female	124,5	2400
K- 07 45 00 72	G 1/8 female	124,0	2400
K- 07 45 00 69	G 1/8 female	154,0	2400