K-WV 3/2 5/2 NAMUR

3/2 and 5/2-way spool valves

Caracteristici

Medii	Air, neutral gases (filtered)
Presiune diferenţială	2 - 10 bar
presiune statică admisă	Max. 10 bar
Temperatura de lucru	-25 °C to +60 °C
Conexiune electrică	Connector socket Pg 9P, 3 x DIN 46244 / VDE 0580
Carcasă	Aluminium, anodised black
Material de etanşare	NBR and PUR



Indicaţie

Alte date sunt disponibile la cerere.

Descriere

Pilot-operated 3/2 and 5/2-way spool valves with threaded port connections and a NAMUR style interface. The two conversion plates supplied with each valve allow the device to be adapted to a 3/2-way or 5/2-way function. The valve is turned on by a continuous signal. Turning off causes the piston to be returned to its initial position under pressure. Includes a manual operator as standard.

Articol

Denumire	Tensiune	Port 1	Conexiunea 3 + 5	DN	Debit (L/min)
K- 07 15 00 01	230 V, 50 Hz	G 1/4	G 1/8	6	700
K- 07 15 00 02	24 V DC	G 1/4	G 1/8	6	700

În pofida controlului minuțios nu putem exclude eventualele informații eronate și nu garantăm pentru datele cuprinse.