

K-DRS MDR 5 O ENTLASTU VENT

»MDR 5« pressure switches, without unloading valve / on/off switch / motor protection circuit, with flange 1/4

HANSA FLEX

Caracteristici

Temperatură mediu	-5 °C to +80 °C
Presiune max. de decuplare	16 bar
Capacitate de întrerupere	5,5 kW
Tip de contact	NC (3-pole)
Frecvență de conectare max.	120 (electrical), 600 (mechanical)
Tip de protecție	IP 54



Indicație

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)

Alte date sunt disponibile la cerere.

Descriere

Three-phase version

Indicații referitoare comandă

For use on devices that have to be vented whenever they are turned off, either because of safety regulations or for technical reasons. The pneumatic devices are disconnected from the system and simultaneously vented each time they are shut off.

Informații suplimentare

Important: A thermal, 3-pole overcurrent relay must be ordered together with these switches. Without this relay, the on/off mechanism does not work.

Articol

Denumire	Racord de aer comprimat	Domeniu de reglare
K- 07 30 24 24	G 1/2	2,0 - 11,0 bar
K- 07 30 24 26	G 1/2	2,5 - 16,0 bar