

K-BKR STANDARD ZWEIFTEILIG VA

Ball valves

HANSA FLEX

Caracteristici

| | |
|------------------------------|---|
| Presiune de lucru | max. 70 bar (depending on temperature and nominal size) |
| 1.1/4" to 1.1/2" | 20 °C: 70 bar, 60 °C: 55 bar, 100 °C: 35 bar, 150 °C: 6 bar, 180 °C: 4 bar, 200 °C: 0 bar |
| 1/4" bis 1" | 20 °C: 70 bar, 60 °C: 65 bar, 100 °C: 45 bar, 150 °C: 7 bar, 180 °C: 4 bar, 200 °C: 0 bar |
| 2" | 20 °C: 60 bar, 60 °C: 40 bar, 100 °C: 30 bar, 150 °C: 5 bar, 180 °C: 4 bar, 200 °C: 0 bar |
| Temperatura de lucru | 200 °C at 0 bar |
| Garnitură de etanșare | 15 % RPTFE (glass fibre reinforced PTFE) |
| Manetă | Stainless steel 1.4301 |



Indicație

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)
Alte date sunt disponibile la cerere.

Descriere

Full bore

Indicații referitoare comandă

For use on devices that have to be vented whenever they are turned off, either because of safety regulations or for technical reasons. The pneumatic devices are disconnected from the system and simultaneously vented each time they are shut off.

Informații suplimentare

G thread acc. DIN EN ISO 228-1

Articol

| Denumire | DN | Filet | A (mm) | B (mm) | L (mm) | Material |
|----------------|----|---------|--------|--------|--------|-------------------------------|
| K- 07 30 00 01 | 8 | G 1/4 | 102,0 | 56,0 | 52,0 | Stainless steel 1.4401/1.4408 |
| K- 07 30 00 02 | 10 | G 3/8 | 102,0 | 56,0 | 52,0 | Stainless steel 1.4401/1.4408 |
| K- 07 30 00 03 | 15 | G 1/2 | 123,0 | 65,0 | 58,0 | Stainless steel 1.4401/1.4408 |
| K- 07 30 00 04 | 20 | G 3/4 | 123,0 | 68,0 | 67,0 | Stainless steel 1.4401/1.4408 |
| K- 07 30 00 05 | 25 | G 1 | 153,0 | 79,0 | 78,0 | Stainless steel 1.4401/1.4408 |
| K- 07 30 00 06 | 32 | G 1 1/4 | 153,0 | 84,0 | 90,0 | Stainless steel 1.4401/1.4408 |
| K- 07 30 00 07 | 40 | G 1 1/2 | 183,0 | 93,0 | 104,0 | Stainless steel 1.4401/1.4408 |
| K- 07 30 00 08 | 50 | G 2 | 183,0 | 99,0 | 127,0 | Stainless steel 1.4401/1.4408 |