

K-BKR LEICHT IG IG

Ball valves, lightweight type, female/female thread

HANSA FLEX

Caracteristici

| | |
|------------------------------|--|
| Domeniul de utilizare | Compressed air, water, non-toxic and non-corrosive gases, heating systems, agriculture |
| Presiune de lucru | Max. 40 bar |
| Temperatura de lucru | -15 °C to +90 °C |
| Descriere filet | G thread acc. DIN EN ISO 228-1 |
| Carcasă | Nickel-plated brass |
| Manetă | Alu, painted black |
| Rulment | Nickel-plated brass |
| Etanșare bilă | PTFE |
| Etanșare ax | HNBR / EPDM / PTFE. 2 O-Rings (HNBR / EPDM) 1 gasket (PTFE) additional PTFE-gasket |



Indicație

Alte date sunt disponibile la cerere.

Articol

| Denumire | DN | Filet | A (mm) | B (mm) | L (mm) |
|----------------|----|---------|-----------|-----------|-----------|
| K- 07 30 00 33 | 8 | G 1/4 | 85,0 | 42,0 | 39,0 |
| K- 07 30 00 34 | 10 | G 3/8 | 85,0 | 42,0 | 43,0 |
| K- 07 30 00 35 | 15 | G 1/2 | 85,0 | 46,0 | 50,0 |
| K- 07 30 00 36 | 20 | G 3/4 | 105,0 | 53,0 | 58,0 |
| K- 07 30 00 37 | 25 | G 1 | 105,0 | 57,0 | 69,0 |
| K- 07 30 00 38 | 32 | G 1 1/4 | 130,0 | 70,0 | 81,0 |
| K- 07 30 00 39 | 40 | G 1 1/2 | 130,0 | 76,0 | 93,0 |
| K- 07 30 00 40 | 50 | G 2 | 165,0 | 92,0 | 110,0 |