

# K-NADELVENTILE MS

Needle valves

**HANSA FLEX**

## Caracteristici

|                   |                      |
|-------------------|----------------------|
| Presiune de lucru | Max. 16 bar          |
| Temperatură       | -30 °C to +110 °C    |
| Garnituri         | NBR                  |
| Carcasă           | Brass                |
| Rotiță de reglare | Plastic              |
| Ax                | With fine adjustment |



## Indicație

Alte date sunt disponibile la cerere.

## Articol

| Denumire       | DN | Filet        | A<br>(mm) | B<br>(mm) | L<br>(mm) | SW<br>(mm) |
|----------------|----|--------------|-----------|-----------|-----------|------------|
| K- 07 30 03 55 | 4  | G 1/4 male   | 48,0      | 50,0      | 45,0      | 17         |
| K- 07 30 03 56 | 4  | G 3/8 male   | 48,0      | 54,0      | 51,0      | 22         |
| K- 07 30 03 57 | 4  | G 1/4 female | 48,0      | 48,0      | 42,0      | 17         |
| K- 07 30 03 58 | 4  | G 3/8 female | 48,0      | 52,0      | 51,0      | 22         |
| K- 07 30 03 59 | 4  | G 1/2 female | 48,0      | 56,0      | 64,0      | 27         |