

# K-SDR DREH AG

Banjo elbows, swivel type, parallel male thread

**HANSA FLEX**

## Caracteristici

Presiune de lucru	Max. 16 bar (at +20 °C)
Temperatura de lucru	-20 °C to +70 °C
Material	Alamă nichelată
Inel de presiune	Hostaform (black nickel-plated for Ø 10, 12)
Inel O	NBR, siliconefree
Clește de prindere	Stainless steel AISI 316



## Indicație

Alte date sunt disponibile la cerere.

## Descriere

Economy yet very high-quality series of push-in fittings made of nickel-plated brass. Compact, space-saving, lightweight design. An O-ring in the fillet at the end of the thread guarantees a tight connection for all male thread parts, even on rough surfaces.

## Articol

Denumire	Filet	pentru Ø exterior furtun	L1 (mm)	L2 (mm)
K- 07 40 29 88	M 5	4 mm	18,5	17,0
K- 07 40 29 91	G 1/8	4 mm	21,0	25,0
K- 07 40 29 92	G 1/8	6 mm	23,5	25,0
K- 07 40 29 93	G 1/8	8 mm	24,5	25,0
K- 07 40 29 89	G 1/4	6 mm	24,5	29,3
K- 07 40 29 90	G 1/4	8 mm	26,0	29,3