


# K-GAM IG 4

Female connectors, female thread

**HANSA FLEX**

## Caracteristici

presiune max. de lucru	18 bar
furtunuri utilizabile	PA, PE, PU
Material	Alamă nichelată



## Indicație

Alte date sunt disponibile la cerere.

## Articol

Denumire	Filet	pentru furtun	L1 (mm)	Deschiderea cheii fixe
K- 07 40 33 77	G 1/8	6 mm / 4 mm	25,0	14 mm
K- 07 40 33 78	G 1/8	8 mm / 6 mm	25,0	14 mm
K- 07 40 33 75	G 1/4	6 mm / 4 mm	29,0	17 mm
K- 07 40 33 76	G 1/4	8 mm / 6 mm	29,0	17 mm
K- 07 40 33 74	G 1/4	10 mm / 8 mm	30,5	17 mm
K- 07 40 33 73	G 1/2	8 mm / 6 mm	33,0	24 mm
K- 07 40 33 72	G 1/2	10 mm / 8 mm	34,5	24 mm
K- 07 40 33 80	G 3/8	6 mm / 4 mm	29,5	20 mm
K- 07 40 33 81	G 3/8	8 mm / 6 mm	29,5	20 mm
K- 07 40 33 79	G 3/8	10 mm / 8 mm	31,0	20 mm