

K-SDR AG

Banjo elbows, parallel male thread

HANSA FLEX

Caracteristici

presiune max. de lucru	18 bar
furtunuri utilizabile	PA, PE, PU
Material	Alamă nichelată



Indicație

Alte date sunt disponibile la cerere.

Articol

Denumire	Filet	pentru furtun	L1 (mm)	L2 (mm)	Deschiderea cheii fixe
K- 07 40 33 99	M 5	5 mm / 3 mm	17,0	17,5	8 mm
K- 07 40 34 00	M 5	6 mm / 4 mm	18,0	17,5	8 mm
K- 07 40 34 04	G 1/8	6 mm / 4 mm	24,0	28,0	14 mm
K- 07 40 34 05	G 1/8	8 mm / 6 mm	24,0	28,0	14 mm
K- 07 40 34 02	G 1/4	6 mm / 4 mm	26,0	29,5	17 mm
K- 07 40 34 03	G 1/4	8 mm / 6 mm	26,0	29,5	17 mm
K- 07 40 34 01	G 1/4	10 mm / 8 mm	27,5	33,0	17 mm
K- 07 40 34 07	G 3/8	8 mm / 6 mm	27,5	31,5	22 mm
K- 07 40 34 06	G 3/8	10 mm / 8 mm	28,5	31,5	22 mm