

K-RD NIPPEL KURZ ES

Reducing nipples, short type

HANSA FLEX

Caracteristici

| | |
|-------------------|----------------------|
| Presiune de lucru | Max. 20 bar |
| Material | Oțel superior 1.4571 |



Indicație

The dimensions of the standard screw fittings may change slightly during the life of the catalogue as a result of optimisation processes.
Alte date sunt disponibile la cerere.

Informații suplimentare

Further types and dimensions on request.

Articol

| Denumire | Filet exterior | Filet interior | L1 (mm) | L2 (mm) | Deschiderea cheii fixe |
|----------------|----------------|----------------|------------|------------|------------------------|
| K- 07 40 15 27 | G 1/8 | M 5 | 11,0 | 7,0 | 14 mm |
| K- 07 40 15 26 | G 1/4 | M 5 | 14,0 | 10,0 | 17 mm |
| K- 07 40 15 28 | G 1/4 | G 1/8 | 13,0 | 8,0 | 17 mm |
| K- 07 40 15 33 | G 3/8 | G 1/8 | 13,0 | 9,5 | 19 mm |
| K- 07 40 15 29 | G 3/8 | G 1/4 | 13,0 | 9,5 | 19 mm |
| K- 07 40 15 35 | G 1/2 | G 1/8 | 18,0 | 12,0 | 24 mm |
| K- 07 40 15 34 | G 1/2 | G 1/4 | 15,5 | 11,5 | 22 mm |
| K- 07 40 15 30 | G 1/2 | G 3/8 | 15,5 | 11,5 | 22 mm |
| K- 07 40 15 36 | G 3/4 | G 3/8 | 18,0 | 12,0 | 32 mm |
| K- 07 40 15 31 | G 3/4 | G 1/2 | 21,0 | 14,0 | 32 mm |
| K- 07 40 15 37 | G 1 | G 1/2 | 24,0 | 16,0 | 36 mm |
| K- 07 40 15 32 | G 1 | G 3/4 | 18,0 | 12,0 | 36 mm |