
## K-PROP VENTIL LU GA 24 V DC

Proportional valves for controlling the flow of air / gas, 24 VDC, closed when de-energised



Caracteristici			
Domeniu de temperaturi	Max. 50 °C (G 1/8), Max. 90 °C (G 1/4, G 3/8)		
Medii	Air, neutral gases, water, oil		
Domeniu de presiune	Vacuum (max. 8 bar)		
Comandă	Via plug amplifier 0 to 10 V, 0 to 20 mA, 4 to 20 mA		
Comportament de autoprotejare	Tight closure in case of loss of voltage		
Carcasă, scaun al supapei	Brass		
Piese interioare	Stainless steel		
Placă port-supapă	FKM		
Material de etanşare	FKM		





## Indicație

Alte date sunt disponibile la cerere.

## **Descriere**

## Informații suplimentare

We recommend combining these proportional valves with a plug amplifier, type K-07250999 or K-07251000 We recommend combining these proportional valves with a plug amplifier, type K-07250999 or K-07251000

Articol						
Denumire	Racord	DN	Diferență max. de presiune de lucru	Α	В	С
			(bar)	(mm)		(mm)
K- 07 25 09 91	G 1/4	2	8	85,0	40,0 mm	95,0
K- 07 25 09 92	G 1/4	3	4	85,0	40,0 mm	95,0
K- 07 25 09 93	G 3/8	6	1	85,0	48,0 mm	97,0
K- 07 25 09 94	G 3/8	7	1	85,0	48,0 mm	97,0

13.11.2025 HANSA-FLEX AG www.hansa-flex.com