
K-PROP VENTIL WA 24 V DC

Proportional valves for controlling the flow of water / oil, 24 VDC, closed when de-energised



Caracteristici		
Domeniu de temperaturi	Max. 50 °C (G 1/8), Max. 90 °C (G 1/4, G 3/8)	
Medii	Air, neutral gases, water, oil	
Domeniu de presiune	Vacuum (max. 8 bar)	
Comandă	Via plug amplifier 0 to 10 V, 0 to 20 mA, 4 to 20 mA	
Comportament de autoprotejare	Tight closure in case of loss of voltage	
Carcasă, scaun al supapei	Brass	
Piese interioare	Stainless steel	
Placă port-supapă	FKM	
Material de etanşare	FKM	





Indicație

Alte date sunt disponibile la cerere.

Descriere

Informații suplimentare

We recommend combining these proportional valves with a plug amplifier, type K-07250999 or K-07251000 We recommend combining these proportional valves with a plug amplifier, type K-07250999 or K-07251000

Articol						
Denumire	Racord	DN	Diferență max. de presiune de lucru	Α	В	С
			(bar)	(mm)		(mm)
K- 07 25 09 95	G 1/4	2	8	85,0	40,0 mm	95,0
K- 07 25 09 96	G 1/4	3	4	85,0	40,0 mm	95,0
K- 07 25 09 97	G 3/8	6	1	85,0	48,0 mm	97,0
K- 07 25 09 98	G 3/8	7	1	85,0	48,0 mm	97,0

18.10.2025 HANSA-FLEX AG www.hansa-flex.com