
## K-HS RD

## Unidirectional banjo valves, pneumatic release, port 2 with female thread



Caracteristici				
Presiune de lucru	0.3 - 10 bar			
Presiune de comandă	0.5 - 2.5 bar, depending on operating pressure			
Temperatură mediu	max. 60 °C			
Poziție de montare	Any. The ring piece must be positioned before the valve is tightened			
Material	Alamă nichelată			
Material de etanșare	Perbunan			





## Indicație

Alte date sunt disponibile la cerere.

## Descriere

For stopping and positioning the cylinder movement: If a control signal is present at port 3 (see drawing), air can flow to and from the cylinder. If no control signal is present, the cylinder exhaust air is shut off by the unidirectional valve. <br/>
The cylinder is stopped. Releasable unidirectional valves are screwed directly onto the cylinder instead of the normal pipe connections.

Articol							
Denumire	Port 1	Port 2	Conexiunea 3	B (****)	C		
K- 07 15 07 04	G 1/8	G 1/8	M 5	(mm) 38,0	(mm) 21,5		
K- 07 15 07 03	G 1/4	G 1/4	G 1/8	43,0	25,4		
K- 07 15 07 05	G 3/8	G 3/8	G 1/8	46,0	31,6		
K- 07 15 07 02	G 1/2	G 1/2	G 1/8	52,0	32,0		