
## K-WKV 3/2 SCHLS SCHNVERSCHR

3/2-way toggle valves, discharge port on thread, quick-lock screw fitting



Caracteristici				
Presiune de lucru	max. 8 bari			
Domeniu de temperaturi	0 °C to +70 °C			
Filet tablou de comandă	M 12 x 0.75 (sheet thickness max. 4 mm)			
Piese interioare	Brass with a bare metal surface			
Material de etanşare	NBR			
Şurub tubular, braţ pivotant, pârghie basculantă	Nickel-plated brass			
Garnituri de etanşare (captive)	Polyamide (glass fibre-reinforced)			





## Indicație

Alte date sunt disponibile la cerere.

## **Descriere**

Manually operated toggle valves, 2/2 and 3/2-way types. For all applications where compressed air must be switched on or off quickly and easily or a cylinder operated manually. Designed as a banjo-type valve with a hollow bolt and ring piece. Suitable for screwing directly into the equipment or for panel mounting. Compact type of construction, also ideal where space is restricted.

Articol							
Denumire	Execuție	C (mm)	pentru furtun	Filet	Deschiderea cheii fixe	B (mm)	
K- 07 15 07 24	3/2-way	16,0	G 1/8 IG	G 1/8	14 mm	55,0	
K- 07 15 07 25	3/2-way	25,0	5 mm / 3 mm	G 1/8	14 mm	55,0	
K- 07 15 07 26	3/2-way	25,0	6 mm / 4 mm	G 1/8	14 mm	55,0	
K- 07 15 07 27	3/2-way	25,0	8 mm / 6 mm	G 1/8	14 mm	55,0	
K- 07 15 07 20	3/2-way	22,0	G 1/4 IG	G 1/4	17 mm	60,0	
K- 07 15 07 22	3/2-way	26,5	6 mm / 4 mm	G 1/4	17 mm	60,0	
K- 07 15 07 23	3/2-way	27,5	8 mm / 6 mm	G 1/4	17 mm	60,0	
K- 07 15 07 21	3/2-way	28,5	10 mm / 8 mm	G 1/4	17 mm	60,0	

14.12.2025 HANSA-FLEX AG www.hansa-flex.com