

Caracteristici			
Medii	Filtered, unlubricated compressed air		
Domeniu de presiune	0 - 7 bar (NC) with silver plate at manual override 0 - 5 bar (NO) with black plate at manual override		
Racord	In manifold base		
Domeniu de temperaturi	-5 °C to +45 °C		
Timp de deschidere/timp de închidere	10 - 12 ms (depending on pressure)		
Putere bobină	2,5 W		
Material	Material plastic		
Material de etanşare	NBR, stainless steel		



Indicație

Alte date sunt disponibile la cerere.

Descriere

Directly controlled 3/2-way solenoid valves specially designed for pneumatic applications. These valves are provided with a flange for assembly on an individual base or multiple manifold base. They feature a monostable manual operator. The scope of supply includes two fixing bolts and a flange gasket. The coils can be turned 180°.

Informații suplimentare

Important: The scope of supply does not include a connector. Please order separately.

Articol

Denumire	Funcția	Tensiune	Racord	Н	В	
				(mm)	(mm)	
K- 07 15 14 18	NC	24 V DC	Cable (30 cm)	42,0	15,0	
K- 07 15 14 19	NC	24 V DC	for system plug	42,0	15,0	
K- 07 15 14 20	NC	12 V DC	Cable (30 cm)	42,0	15,0	
K- 07 15 14 21	NC	12 V DC	for system plug	42,0	15,0	
K- 07 15 14 22	NO	24 V DC	Cable (30 cm)	42,0	15,0	
K- 07 15 14 23	NO	24 V DC	for system plug	42,0	15,0	
K- 07 15 14 24	NO	12 V DC	Cable (30 cm)	42,0	15,0	
K- 07 15 14 25	NO	12 V DC	for system plug	42,0	15,0	