

# K-PNEU LOGIKELEMENTE

Pneumatic logic elements

**HANSA FLEX**

## Caracteristici

Presiune de lucru	OR-AND: 1.5-8 bar, NOT: 0.4-6 bar, YES - MEMORY: 0.0-8 bar (pilot pressure from 1.5-8 bar)
Domeniu de temperaturi	-10 °C to +60 °C
Racord	Push-in fitting for 4 mm pipe
Debit	100 l/min (at 6 bar and $\Delta p = 1$ bar)
Ø nominal	2,7 mm
Revenire	OR - AND: by compressed air, MEMORY: by air, YES - NOT: by mechanical spring
Material	Technopolymer
Vană	Aluminium
Material de etanşare	NBR



## Indicație

Alte date sunt disponibile la cerere.

## Descriere

Pneumatic logic elements are available with five different functions: OR, AND, NOT, YES, MEMORY. All elements have an adapter for the  $\Omega$ -rail (DIN EN 50022) integral with the body.

## Articol

Denumire	Funcția	Înălțime (mm)	Lungime (mm)
K- 07 15 13 77	OR	40	38,5
K- 07 15 13 78	AND	40	38,5
K- 07 15 13 79	NOT	40	55,2
K- 07 15 13 80	YES	40	55,2
K- 07 15 13 81	MEMORY	41	89,5