K-KURZH ZYL EINFACHW


Short-stroke cylinders, single-acting (magnetic)

HANSA-FLEX

Caracteristici

Medii	Filtered compressed air, lubricated (ensure continuity) or unlubricated
Presiune de lucru	max. 10 bari
Presiune de acţionare	0,6 bar (Ø 12 bis Ø 32), 0,4 bar (Ø 40 bis Ø 80)
Domeniu de temperaturi	-10 °C to +80 °C
Tija piston	C45 steel, hard chrome-plated
Ţeavă	Aluminium alloy, anodised
Diametru cap	Ø 12 to Ø 25 painted brass, Ø 32 to Ø 80 aluminium
Piston	Ø 12 to Ø 63 synthetic (acetal) resin, Ø 80 alu/ PTFE
Garnitură la tija pistonului	NBR (additional charge for PU and FKM)
Garnitură piston	NBR (additional charge for PU and FKM)





Indicaţie

Alte date sunt disponibile la cerere.

Descriere

Suitable for installation in limited spaces, with magnet.

Informaţii suplimentare

Important: The scope of supply does not include a connector. Please order separately.

Other types, e.g. increased thermal stability, non-standard strokes, through rod, non-rotating version, etc., available on request.

Articol

Denumire	Ø piston	Cursa (mm)	Racord	Filet interior la tija pistonului
K- 07 15 11 87	12 mm	10	M 5	M 3
K- 07 15 11 88	12 mm	25	M 5	M 3
K- 07 15 11 89	16 mm	10	M 5	M 5
K- 07 15 11 90	16 mm	25	M 5	M 5
K- 07 15 11 91	20 mm	10	M 5	M 5
K- 07 15 11 92	20 mm	25	M 5	M 5
K- 07 15 11 93	25 mm	10	G 1/8	M 5
K- 07 15 11 94	25 mm	25	G 1/8	M 5
K- 07 15 11 95	32 mm	10	G 1/8	M 6
K- 07 15 11 96	32 mm	25	G 1/8	M 6
K- 07 15 11 97	40 mm	10	G 1/8	M 6
K- 07 15 11 98	40 mm	25	G 1/8	M 6
K- 07 15 11 99	50 mm	25	G 1/8	M 8
K- 07 15 12 00	63 mm	25	G 1/8	M 8

Accesorii

K-MAGNETSENSOREN-REED	Reed magnetic sensor (incl. 2.5 m cable)

În pofida controlului minuţios nu putem exclude eventualele informaţii eronate şi nu garantăm pentru datele cuprinse.