
K-STOPPVENTILE STECK

Stop valves, ports 2 and 3 with plug connection



Caracteristici					
Presiune de lucru	Max. 10 bar				
Presiune de comandă	1 - 5 bar, depending on operating pressure				
Temperatură mediu	max. 70 °C				
Poziție de montare	Any. Ring pieces can still be rotated 360° after the valve has been tightened				
Material de etanșare	Perbunan				





Indicație

Alte date sunt disponibile la cerere.

Descriere

For high-speed positioning and stop functions as well as emergency switching (e.g. emergency stop). If a control signal is present at port 3, air can flow to and from the cylinder. If no control signal is present, the air flow to and from the cylinder is shut off, causing the cylinder to stop in the required position. Stop valves are screwed directly onto the cylinder instead of the normal pipe connections.

Articol						
Denumire	Port 1	Port 2	Conexiunea 3	Material	B (mm)	C (mm)
K- 07 15 20 50	G 1/8	6 mm	4 mm	Nickel-plated brass	52,0	25,0
K- 07 15 20 49	G 1/4	6 mm	4 mm	Nickel-plated brass	58,0	28,0
K- 07 15 20 51	G 3/8	8 mm	4 mm	Nickel-plated brass	63,0	32,0
K- 07 15 20 48	G 1/2	12 mm	4 mm	Nickel-plated brass	72,0	41,0