

# K-WV 3/2 MANU L DREHHEBEL

3/2-way pilot valves, manually operated, with long wing lever, NC

**HANSA FLEX**

## Caracteristici

|                         |   |
|-------------------------|---|
| Presiune de lucru       | 2.5 - 10 bar (monostable)\n1.0 - 10 bar (bistable)\nMax. vacuum 10 bar (external pilot air) |
| Domeniu de temperaturi  | -10 °C to +60 °C  |
| Debit 6 bari și 10 bari | 550 NI/min  |
| Debit 6 bari și 5 bari  | 400 NI/min  |
| Corp de supapă          | Aluminiu  |
| Arc                     | Special steel   |
| Piston                  | Aluminium   |
| Material de etanșare    | NBR   |



## Indicație

3 valve positions only in conjunction with a second 3/2-way valve. <br>Corresponds to a 5/3-way valve.  
Alte date sunt disponibile la cerere.

## Informații suplimentare

Important: The scope of supply does not include a connector. Please order separately.

## Articol

| Denumire       | Racord | Simbol | Aționare   | Poziții de cuplare |
|----------------|--------|--------|------------|--------------------|
| K- 07 15 00 82 | G 1/8  | 9      | monostable | 2                  |
| K- 07 15 00 83 | G 1/8  | 10     | bistabil   | 2                  |
| K- 07 15 00 84 | G 1/8  | 11     | monostable | 3*                 |
| K- 07 15 00 85 | G 1/8  | 12     | bistabil   | 3*                 |