K-WV 3/2 MANU L DREHHEBEL

3/2-way pilot valves, manually operated, with long wing lever, NC

Caracteristici

Presiune de lucru	2.5 - 10 bar (monostable)\n1.0 - 10 bar (bistable)\nMax. vacuum 10 bar (external pilot air)
Domeniu de temperaturi	-10 °C to +60 °C
Debit 6 bari şi 10 bari	550 Nl/min
Debit 6 bari şi 5 bari	400 Nl/min
Corp de supapă	Aluminiu
Arc	Special steel
Piston	Aluminium
Material de etanşare	NBR



Indicaţie

3 valve positions only in conjunction with a second 3/2-way valve.
Corresponds to a 5/3-way valve.
Alte date sunt disponibile la cerere.

Informaţii suplimentare

Important: The scope of supply does not include a connector. Please order separately.

Articol

Denumire	Racord	Simbol	Acţionare	Poziţii de cuplare
K- 07 15 00 82	G 1/8	9	monostable	2
K- 07 15 00 83	G 1/8	10	bistabil	2
K- 07 15 00 84	G 1/8	11	monostable	3*
K- 07 15 00 85	G 1/8	12	bistabil	3*

În pofida controlului minuţios nu putem exclude eventualele informaţii eronate şi nu garantăm pentru datele cuprinse.