# K-WV 5/2 MANU K DREHHEBEL

5/2-way pilot valves, manually operated, with short wing lever

## Caracteristici

| | |
|---|---|
| **Presiune de lucru** | 2.5 - 10 bar (monostable)\n1.0 - 10 bar (bistable)\nMax. vacuum 10 bar (external pilot air) |
| **Domeniu de temperaturi** | -10 °C to +60 °C |
| **Debit 6 bari şi 10 bari** | 550 Nl/min |
| **Debit 6 bari şi 5 bari** | 400 Nl/min |
| **Corp de supapă** | Aluminiu |
| **Arc** | Special steel |
| **Piston** | Aluminium |
| **Material de etanşare** | NBR |



## Indicaţie

*3 valve positions only in conjunction with a second way valve.
Alte date sunt disponibile la cerere.

## Informaţii suplimentare

Important: The scope of supply does not include a connector. Please order separately.

## Articol

| Denumire | Racord | Simbol | Acţionare | Poziţii de cuplare |
|---|---|---|---|---|
| **K- 07 15 02 37** | G 1/8 | 5 | monostable | 2 |
| **K- 07 15 02 38** | G 1/8 | 6 | bistabil | 2 |
| **K- 07 15 02 39** | G 1/8 | 7 | monostable | 3* |
| **K- 07 15 02 40** | G 1/8 | 8 | bistabil | 3* |

*În pofida controlului minuțios nu putem exclude eventualele informații eronate și nu garantăm pentru datele cuprinse.*