


K-FI MIKRO M DIFFERENZ MANO

Micro-filters with differential pressure gauge

HANSA FLEX

Caracteristici

Presiune de intrare	Min. 4 bar, Max. 16 bar
Domeniu de afișare manometru pentru presiune diferențială	0 - 2 bar
Carcasă, recipient cu filtru	Aluminium
Temperatură ambientală	+5 °C to +60 °C
Finețea filtrului	0,01 μm
Randament	99.9999 %
Cartuș de filtru	Borosilicate (with glass-fibre and foam plastic)
Măsurarea valorii debitului	At P1 = 6 bar and pressure drop $\Delta p = 1.5\%$



Indicație

Alte date sunt disponibile la cerere.

Descriere

Suitable for all applications where the standard centrifugal separators do not afford the desired efficiency. The pre-filters and micro-filters are equipped with an automatic drain valve. All devices can be supplied with or without a differential pressure gauge. The differential pressure gauge indicates the degree of contamination of the filter element as a function of the pressure drop.

Articol

Denumire	Filet	Debit (L/min)	A (mm)	B1 (mm)	B2 (mm)	C (mm)	D (mm)
K- 07 25 13 02	G 1/4	1300	82,5	407,0	335,0	57,0	353,0
K- 07 25 13 03	G 3/8	1300	82,5	407,0	335,0	57,0	353,0
K- 07 25 13 04	G 1/2	1300	82,5	407,0	335,0	57,0	353,0
K- 07 25 13 05	G 3/4	2000	82,5	477,0	405,0	57,0	493,0
K- 07 25 13 06	G 1	4080	118,0	492,0	420,0	72,0	458,0
K- 07 25 13 07	G 1 1/4	4580	118,0	592,0	520,0	72,0	658,0
K- 07 25 13 08	G 1 1/2	6500	118,0	692,0	620,0	72,0	858,0
K- 07 25 13 09	G 2	9000	118,0	882,0	810,0	72,0	1238,0

Piese de schimb

K-FILTERELEMENT SONDER	Filter element
K-VERBINDUNGSELEMENTE SOND	Connecting sets
K-HALTERBAUSATZ	Holder
K-DIFFERENZDRUCKMANOMETER	Differential pressure gauge
K-AUTOMAT ABLASSVENTIL	Automatic drain valve