

# K-LKM S NW7,6 IG

Safety couplings DN 7.6, female

## Caracteristici

Presiune de lucru	Max. 16 bar
Debit aer	2.250 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Temperatură mediu	-20 °C to +100 °C
Material	Galvanised steel / brass
Arc	Stainless-steel
Material de etanșare	NBR



## Indicație

Alte date sunt disponibile la cerere.

## Descriere

High-quality, robust and durable, one-hand quick disconnect safety couplings, with very high flow rates and only a small pressure drop. The coupling is released fully automatically in two steps. Air is relieved from the coupling before it is completely disconnected, to minimise the risk of injury to the operator from hose ends flying around. The plug is only disconnected from the coupling if the residual pressure has dropped below 0.3 bar. The dreaded "whiplash effect" is thus avoided and the risk of injury virtually eliminated. This safety version conforms to ISO-Standard DIN EN ISO 4414.

## Articol

Denumire	Racord	Lungime (mm)	SW (mm)
K- 07 35 13 20	G 1/4 female	57,1	20
K- 07 35 13 22	G 3/8 female	60,1	22
K- 07 35 13 17	G 1/2 female	59,5	25

## Elemente adiționale

K-NIPPEL KUPPL NW7 AG VZ PTFE	Plugs for couplings DN 7.2 - DN 7.8, hardened and galvanised steel, male threaded, FPM (PTFE coated) seal
K-NIPPEL KUPPL NW7 IG VZ 1	Plugs for couplings DN 7.2 - DN 7.8, hardened and galvanised steel, female
K-NIPPEL KUPPL STREAM LINE	Plugs for couplings DN 7.2 - DN 7.8, hardened and galvanised steel »stream line«
K-TUE 7,2 7,8 ST VZ 2	Stems for couplings DN 7.2 - DN 7.8, hardened and galvanised steel