## K-SPIR SCHL KUPPL SET SVKM

Spiral hose and coupling kits, with quick disconnect couplings DN 7.6



Caracteristici	
Presiune de lucru	10 bar
Temperatură mediu	-20 °C to +60 °C



## Indicație

Alte date sunt disponibile la cerere.

## **Descriere**

Couplings: High-grade single-handed quick-release coupling and safety coupling in steel / brass zinc-plated for high flow rates, specially designed for all applications with high mechanical wear. Strong, impact- and vibration-resistant construction for challenging applications. Polyurethane hose Exceedingly flexible, extremely kink-resistant and tolerant of dirt spiral hose with high resilience under tear, tensile and impact loads with a long service life and outstanding ageing qualities. It is also UV resistant and has outstanding abrasion resistance.

Articol					
Denumire	Dimensiune furtun	Ø spirală <sub>(mm)</sub>	Lungime de lucru		
K- 07 10 07 59	10 mm x 6,5 mm	52	4,0		
K- 07 10 07 60	10 mm x 6,5 mm	52	6,0		
K- 07 10 07 61	10 mm x 6,5 mm	52	8,0		
K- 07 10 07 62	12 mm x 8 mm	65	4,0		
K- 07 10 07 63	12 mm x 8 mm	65	6,0		
K- 07 10 07 64	12 mm x 8 mm	65	8,0		

02.12.2025 HANSA-FLEX AG www.hansa-flex.com