

K-SPIR SCHL KUPPL SET LKM NW 7,6

Spiral hose and coupling kits, with safety couplings DN 7.6

HANSA FLEX

Caracteristici

| | |
|-------------------|------------------|
| Presiune de lucru | 10 bar |
| Temperatură mediu | -20 °C to +60 °C |



Indicație

Alte date sunt disponibile la cerere.

Descriere

Couplings: High-grade single-handed quick-release coupling and safety coupling in steel / brass zinc-plated for high flow rates, specially designed for all applications with high mechanical wear. Strong, impact- and vibration-resistant construction for challenging applications. Polyurethane hose Exceedingly flexible, extremely kink-resistant and tolerant of dirt spiral hose with high resilience under tear, tensile and impact loads with a long service life and outstanding ageing qualities. It is also UV resistant and has outstanding abrasion resistance.

Articol

| Denumire | Dimensiune furtun | Ø spirală (mm) | Lungime de lucru (m) |
|----------------|-------------------|-------------------|-------------------------|
| K- 07 10 07 65 | 10 mm x 6,5 mm | 52 | 2,0 |
| K- 07 10 07 66 | 10 mm x 6,5 mm | 52 | 4,0 |
| K- 07 10 07 67 | 10 mm x 6,5 mm | 52 | 6,0 |
| K- 07 10 07 68 | 10 mm x 6,5 mm | 52 | 8,0 |
| K- 07 10 07 69 | 12 mm x 8 mm | 65 | 2,0 |
| K- 07 10 07 70 | 12 mm x 8 mm | 65 | 4,0 |
| K- 07 10 07 71 | 12 mm x 8 mm | 65 | 6,0 |
| K- 07 10 07 72 | 12 mm x 8 mm | 65 | 8,0 |