

# K-MV G (NC) D 230 V, 50 HZ STA

Normally closed, (NC), directly operated, 230 V, 50 Hz, standard type

**HANSA FLEX**

## Caracteristici

|                                  |   |
|----------------------------------|---|
| <b>Conexiune electrică</b>       | device socket type A in acc. with ISO 4400 for all valves with threads G 3/8 & G 1/2, except valves type 3 & 4. Device socket |
| <b>Tip de protecție</b>          | IP 65   |
| <b>Temperatură mediu</b>         | max. 80 °C when using water or oils; max. 90 °C when using with air   |
| <b>Descriere filet</b>           | G thread acc. DIN EN ISO 228-1  |
| <b>Carcasă, scaun al supapei</b> | Brass   |
| <b>Piese interioare</b>          | Stainless steel   |
| <b>Garnitură de etanșare</b>     | FPM   |



## Indicație

Alte date sunt disponibile la cerere.

## Descriere

Standard series in two different versions: Directly operated, Pilot-operated. For all applications with compressed air, neutral gases or low-viscosity, neutral media.

## Articol

| Denumire       | Filet | presiune max. de lucru (bar) | NW  | A (mm) | B (mm) | C (mm) | Forma constructivă |
|----------------|-------|------------------------------|-----|--------|--------|--------|--------------------|
| K- 07 30 01 56 | G 1/8 | 10                           | 3,0 | 70,0   | 40,0   | 70,7   | 1                  |
| K- 07 30 01 57 | G 1/4 | 10                           | 3,0 | 70,0   | 40,0   | 70,7   | 1                  |
| K- 07 30 01 58 | G 3/8 | 10                           | 5,0 | 85,0   | 52,0   | 87,0   | 1                  |
| K- 07 30 01 59 | G 1/2 | 10                           | 5,0 | 85,0   | 52,0   | 87,0   | 1                  |