


K-MV O (NO) D 230 V, 50 HZ STA VA

Normally open, (NO), directly operated, 230 V, 50 Hz, standard type VA



Caracteristici	
Conexiune electrică	device socket type A in acc. with ISO 4400 for all valves with threads G 3/8 & G 1/2, except valves type 3 & 4. Device socket
Descriere filet	G thread acc. DIN EN ISO 228-1
Temperatură mediu	max. 80 °C when using water or oils; max. 90 °C when using with air
Tip de protecție	IP 65
presiune max. de lucru	7 bar
Material de etanșare	FPM
Carcasă, scaun al supapei	Stainless steel 1.4301
Piese interioare	Stainless steel



Indicație
Alte date sunt disponibile la cerere.

Descriere
Standard series in two different versions: Directly operated, Pilot-operated

Articol						
Denumire	Filet	NW	A (mm)	B (mm)	C (mm)	Forma constructivă
K- 07 30 01 34	G 1/8	3,0	70,0	40,0	76,0	2
K- 07 30 01 35	G 1/4	3,0	70,0	40,0	76,0	2
K- 07 30 01 36	G 3/8	5,0	85,0	52,0	92,0	2
K- 07 30 01 37	G 1/2	5,0	85,0	52,0	92,0	2