K-ENDLAGEN-RUECKME KUNST S

End position feedback plastic- inductive sensors

Caracteristici

Curent de lucru	200 mA
Îmbinare cablu prin înşurubare	M 20 x 1.5
Funcţie de comutare	Positive switching, PNP NO contact, damped or undamped in the end position
Tip de protecţie	IP 67, acc. to DIN EN 60529
Domeniu de temperaturi	-20 °C to +70 °C
Carcasă	Polyamide blue or black
Şurub	Stainless steel 1.4301
Arbore	Polyamide PA6, black
Capac	Polycarbonate, transparent
Punte de montaj	PA6 with 30 % glass fibre
Garnituri	EPDM and NBR
Material de etanşare	NBR



Indicaţie

Alte date sunt disponibile la cerere.

Descriere

Robust type in a plastic housing, Universal indicator for NAMUR sizes 80 x 30 and 130 x 30, Height-adjustable feet that adapt to different pinion projections, ON / OFF position indicator also visible from a distance, Easy-to-adjust, self-locking trip cam

Articol

Denumire	Tensiune	Definiţie
K- 07 30 29 06	9 V - 36 V DC	End position feedback, D 2 type with inductive 3-wire sensors

În pofida controlului minuţios nu putem exclude eventualele informaţii eronate şi nu garantăm pentru datele cuprinse.